


Hebelarmkupplungen DIN 2828 mit Innengewinde / Väterteil

Gewinde Vulkollan (Ms,AL), PTFE (nr.St),
Kupplung NBR (MS, AL), Hypalon (nr.St)



Größe	Gewinde	Werkstoff	Gewicht	Dichtform	Artikelnummer
			kg		
1/2"	G 1/2"	SS	0,06	fld.	850.050050.120
1/2"	G 1/2"	Ms	0,07	fld.	850.050050.130
1/2"	G 1/2"	Al	0,02	fld.	850.050050.140
3/4"	G 3/4"	SS	0,12	fld.	850.075075.120
3/4"	G 3/4"	Ms	0,13	fld.	850.075075.130
3/4"	G 3/4"	Al	0,04	fld.	850.075075.140
1"	G 1"	SS	0,20	fld.	850.100100.120
1"	G 1"	Ms	0,19	fld.	850.100100.130
1"	G 1"	Al	0,08	fld.	850.100100.140
1"	G 1"	Pp	0,02	Gew.	850.100100.150
1 1/4"	G 1 1/4"	SS	0,24	fld.	850.125125.120
1 1/4"	G 1 1/4"	Ms	0,26	fld.	850.125125.130
1 1/4"	G 1 1/4"	Al	0,08	fld.	850.125125.140
1 1/2"	G 1 1/2"	SS	0,33	fld.	850.150150.120
1 1/2"	G 1 1/2"	Ms	0,42	fld.	850.150150.130
1 1/2"	G 1 1/2"	Al	0,12	fld.	850.150150.140
1 1/2"	G 1 1/2"	Pp	0,07	Gew.	850.150150.150
2"	G 2"	SS	0,48	fld.	850.200200.120
2"	G 2"	Ms	0,46	fld.	850.200200.130
2"	G 2"	Al	0,16	fld.	850.200200.140
2"	G 2"	Pp	0,10	Gew.	850.200200.150
2 1/2"	G 2 1/2"	SS	0,96	fld.	850.250250.120
2 1/2"	G 2 1/2"	Ms	0,98	fld.	850.250250.130
2 1/2"	G 2 1/2"	Al	0,29	fld.	850.250250.140
3"	G 3"	SS	1,35	fld.	850.300300.120
3"	G 3"	Ms	1,30	fld.	850.300300.130
3"	G 3"	Al	0,32	fld.	850.300300.140
4"	G 4"	SS	2,15	fld.	850.400400.120
4"	G 4"	Ms	1,70	fld.	850.400400.130
4"	G 4"	Al	0,48	fld.	850.400400.140